

124

Height of Sliding Panel

H = Floor to Ceiling Height

H1 = Giass Height of Sliding

H1=H-(75+12)

CARRINGE ROLLER

R. RELAR Quality Architectural Hardware Specialist

IRACK (38x36)

CARRIAGE ROLLER

© 2023 ESTRON MARKETING PTE. LTD.


F


FLOOR GUIDE



- For one or more door leaves with or without side panels
- Suitable for 6mm to 8mm thick tempered glass
- Gentle, easy action and glass cut-out is required
- Maximum weight per door leaf: 20kg

TECHNICAL DRAWINGS:





COMPLETE SET:

GLASS PREPARATION


1x Aluminum Track
1500mm (RT-020-1500)2x Carriage Rollers (SDS-020-CR)
2x Glass Clamps (SDS-020-GC)2x End Stopper (SDS-020-ST)
1x Floor Guide (FG-0608)






- For one or more door leaves with or without side panels
- Suitable for 8mm to 10mm thick tempered glass
- Gentle, easy action and glass cut-out is required
- Maximum weight per door leaf: 40kg

TECHNICAL DRAWINGS:





COMPLETE SET:

GLASS PREPARATION









- For one or more door leaves with or without side panels
- Suitable for 8mm to 12mm thick tempered glass
- Gentle, easy action and no glass preparation
- Maximum weight per door leaf: 45kg

TECHNICAL DRAWINGS:



NO GLASS PREPARATION REQUIRED!











- For one or more door leaves with or without side panels
- Suitable for 8mm to 12mm thick tempered glass
- Gentle, easy action and no glass preparation
- Maximum weight per door leaf: 90kg

TECHNICAL DRAWINGS:



NO GLASS PREPARATION REQUIRED!

PSB Tested for 100,000 cycles endurance











- For one or more door leaves with or without side panels
- Suitable for 8mm to 10mm thick tempered glass
- Gentle, easy action
- Maximum weight per door leaf: 80kg

TECHNICAL DRAWINGS:













- For one or more door leaves with or without side panels
- Suitable for 8mm to 12mm thick tempered glass
- Gentle, easy action
- Maximum weight per door leaf: 80kg

TECHNICAL DRAWINGS:





COMPLETE SET:


ESTRON







(For Wooden Doors)











- For one or more door leaves with or without side panels
- Suitable for 10mm to 13.52mm thick tempered glass
- Glass preparation is recommended when install on laminated glass
- Gentle, easy action and no glass preparation
- Maximum weight per door leaf: 100kg
- Also available in Black

TECHNICAL DRAWINGS:



NO GLASS PREPARATION REQUIRED!

PSB Tested for 100,000 cycles endurance



SECTONAL DETAILS









- For one or more door leaves with or without side panels
- Suitable for 10mm to 13.52mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is recommended when install on laminated glass
- Maximum weight per door leaf: 120kg
- Slanted Track and Roller System, minimizes the trapping of dust
- Also available in Black

TECHNICAL DRAWINGS:








SECTONAL DETAILS







(For Wooden Doors)












- For one or more door leaves with or without side panels
- Suitable for 10mm to 13.52mm thick tempered glass
- Maximum weight per door leaf: 120kg ٠
- Stainless Steel Glass Clamp SS304, Satin Finish (SSS)

TECHNICAL DRAWINGS:








SECTONAL DETAILS

COMPLETE SET:

ESTRON









- For one or more door leaves with or without side panels
- Suitable for 10mm to 15.52mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is required for laminated glass installation.
- Maximum weight per door leaf: 150kg

TECHNICAL DRAWINGS:



NO GLASS PREPARATION REQUIRED!

PSB Tested for 100,000 cycles endurance



(Heavy Duty)

SECTONAL DETAILS









(Heavy Duty)

FEATURES

- For one or more door leaves with or without side panels
- Suitable for 10mm to 15.52mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is required for laminated glass installation.
- Maximum weight per door leaf: 180kg

TECHNICAL DRAWINGS:












(Heavy Duty)

FEATURES

- For one or more door leaves with or without side panels
- Suitable for 12mm to 15.52mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is recommended for Laminated Glass and glass height of more than 3600mm.
- Maximum weight per door leaf: 300kg

TECHNICAL DRAWINGS:












- For one or more door leaves with or without side panels
- Suitable for 10mm to 12mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is required for laminated glass installation.
- Maximum weight per door leaf: 100kg


TECHNICAL DRAWINGS:

Glass Clamp Position (With Stopper)










(Telescopic)

Accessories shown in above drawing is for reference only. Cover and Track RT-1220 is not included

Height of Sliding Panel: H1=H-(76+12) H=Floor to Ceiling Height H1=Glass Height of Sliding Panel



COMPLETE SET:





Г

Г

Г Г





(Heavy Duty Telescopic)

FEATURES

- For one or more door leaves with or without side panels
- Suitable for 10mm to 12mm thick tempered glass
- Glass preparation depends on different types of layout, please consult us upon ordering.
- Maximum weight per door leaf: 120kg
- Stainless Steel Glass Clamp SS304, Satin Finish (SSS)

TECHNICAL DRAWINGS:






Accessories shown in above drawing is for reference only. Cover and Track RT-1220 is not included







- For one or more door leaves with or without side panels
- Suitable for 10mm to 12mm thick tempered glass
- Gentle, easy action and no glass preparation
- Glass preparation is required for laminated glass installation.
- Maximum weight per door leaf: 150kg


TECHNICAL DRAWINGS:

















Estron Marketing Pte. Ltd.

141 Woodlands Industrial Park E5 E-terrace Singapore 757507 tel. +65 6853 9041 fax. +65 6853 9042 e-mail. sales@estron.com.sg url. www.estron.com.sg









Product improvement is a continuous process, please check specifications at point of purchase.